



- Directional Antennas
- Omni-directional Antennas
- Vhf Antenna
- VHF - AIS Antennas
- VHF - GPS Antennas
- Coaxial cable
- Connectors
- Phone and TV sockets
- Antenna supports
- Marine Stereos
- Speakers
- Watertight Speakers
- Amagnetic Speakers



Supplied accessories:

- control unit 12v
- 10 m (33') coaxial cable
- 1,5 m (5') coaxial cable
- high thickness synthetic rubber gasket

PANDORA "NEO" SATELLITE ANTENNA

Pandora "NEO" is the new wireless control FULL-HD/4K satellite TV antenna with 39cm (15") dish. The "NEO" antennas are equipped with a super fast satellite locking system even in extreme rough sea conditions thanks to totally renewed electronics and mechanics: more powerful processor, faster driver and more robust structure. Furthermore, the new electronics have been designed to make Pandora "NEO" super silent, both in the satellite search phase and in the tracking phase. Thanks to the introduction of a brand new GPS system, Pandora "NEO" saves previous navigation positions, as well as guarantee increased signal reception performance even at the edges of the signal coverage area. Like all new Glomex "NEO" satellite TV antennas, Pandora "NEO" is managed via the free App available for iOS and Android devices. By downloading the app, you can manage the "NEO" satellite TV antennas in one click via Bluetooth® with your own smartphone/tablet and:

- update the satellites list
- update the antenna
- select and change satellites
- send the operating parameters of the antenna to technical assistance in case of need

| | | | |
|-------------------|---------------------|--------------------------|---|
| Technology | DVB-sS2 4k FULL HD | LNB frequency range | 10,7 - 12,75 Ghz LNB universal |
| Dish diameter | 390 mm (15") | Radome type | U.V. resistant |
| Radome dimensions | 420x450 mm (16x18") | Power requirement | 12 vdc |
| LNB | Universal single | Operating temp. range | -20° +55° |
| App | Yes | Azimuth | Unlimited |
| Coax cable | 1 | Elevation | 0° / 90° |
| Receiver output | 1 | Type of stabilization | Gyro on 2 axis + 3° axis by interpolation |
| Weight | 6 kg (13.3 lb) | Satellite identification | NIT (Network Information Table) |
| Tracking | 50° sec | Min Eirp | 50 dBW |
| Gain | 33 db (12 Ghz) | Future Upgrades ready | Yes |
| Skew | Manual | Control unit | Unlimited |
| Dish type | Prime Focus + HPD | | |
| Polarization | Linear (H+V) | | |

RE 95208



RHEA "NEO" SATELLITE ANTENNA

"Rhea "NEO" is the new wireless control FULL-HD / 4K satellite TV antenna with 47cm (18") dish. The "NEO" antennas are equipped with a super-fast satellite locking system even in extreme rough sea conditions thanks to totally renewed electronics and mechanics: more powerful processor, faster driver and more robust structure.

Furthermore, the new electronics have been designed to make Rhea "NEO" super silent, both in the satellite search phase and in the tracking phase. Thanks to the introduction of a brand-new GPS system, Rhea "NEO" saves previous navigation positions, as well as guarantee increased signal reception performance even at the edges of the signal coverage area. Like all new Glomex "NEO" satellite TV antennas, Rhea "NEO" is managed via the free App available for iOS and Android devices.

By downloading the app, you can manage the "NEO" satellite TV antennas in one click via Bluetooth® with your own smartphone/tablet and:

- update the satellites list;
- update the antenna;
- select and change satellites;
- send the operating parameters of the antenna to technical assistance in case of need.

| | | | |
|-------------------|-----------------------|--------------------------|---|
| Technology | DVB-sS2 4k FULL HD | LNB frequency range | 10,7 - 12,75 Ghz LNB universal |
| Dish diameter | 470 mm (18") | Radome type | U.V. resistant |
| Radome dimensions | 500 x 560 mm (20x22") | Power requirement | 12/24 Vdc |
| LNB | Universal single | Operating temp. range | -20° +55° |
| App | Yes | Azimuth | Unlimited |
| Coax cable | 1 | Elevation | 0° / 90° |
| Receiver output | 1 | Type of stabilization | Gyro on 2 axis + 3° axis by interpolation |
| Weight | 13 kg (28.5 lb) | Satellite identification | NIT (Network Information Table) |
| Tracking | 50° sec | Min Eirp | 49 dBW |
| Gain | 35 db (12 Ghz) | Future Upgrades ready | Yes |
| Dish type | Prime Focus + HPD | Control unit | Unlimited |
| Polarization | Linear (H+V) | | |

RE 95205



SATURN 4 DCSS "NEO" SATELLITE ANTENNA

Saturn 4 "NEO" DCSS is the new FULL-HD/4K wirelessly controlled satellite TV antenna with 47cm disc to use up to 16 TVs simultaneously. Developed with the dCSS / SCR technology, Saturn 4 "NEO" DCSS has been specially manufactured to be used with the dCSS decoders, for example the Sky Q decoders, and to exploit all their features (such as recording a program while watching a other channel). The dCSS technology also has the great advantage of making installation extremely simple and fast thanks to a single cable that comes down from the antenna even for multi-output installations. Like all Glomex "NEO" satellite TV antennas, Saturn 4 is equipped with a super fast satellite locking system even in extreme rough sea conditions thanks to totally renewed electronics and mechanics: more powerful processor, faster driver and more robust. Furthermore, the new electronics have been designed to have extremely quiet satellite TV antennas, both in the satellite search phase and in the tracking phase. Thanks to the introduction of a brand new GPS system, the new "NEO" satellite TV antennas save the previous the navigation positions and guarantee increased signal reception performance even at the edges of the signal coverage area. Saturn 4 "NEO" is managed through the free Glomex SAT TV App available for iOS and Android devices.

| | | | |
|-------------------|-----------------------|--------------------------|---|
| Technology | DVB-sS2 4k FULL HD | LNB frequency range | 10,7 - 12,75 Ghz LNB universal |
| Dish diameter | 470 mm (18") | Radome type | U.V. resistant |
| Radome dimensions | 500 x 560 mm (20x22") | Power requirement | 12 Vdc |
| LNB | Universal single | Operating temp. range | -20° +55° |
| App | Yes | Azimuth | Unlimited |
| Coax cable | 1 | Elevation | 0° / 90° |
| Receiver output | 1/16 | Type of stabilization | Gyro on 2 axis + 3° axis by interpolation |
| Weight | 13 kg (28.5 lb) | Satellite identification | NIT (Network Information Table) |
| Tracking | 50° sec | Min Eirp | 49 dBW |
| Gain | 35 db (12 Ghz) | Future Upgrades ready | Yes |
| Dish type | Prime Focus + HPD | Control unit | Unlimited |
| Polarization | Linear (H+V) | | |



By downloading the app, you can manage the "NEO" satellite TV antennas in one click via Bluetooth® with your own smartphone/tablet and:

- update the satellites list
- update the antenna
- select and change satellites
- send the operating parameters of the antenna to technical assistance in case of need.

RE95206

MARS 4 DCSS "NEO" SATELLITE ANTENNA

Mars 4 "NEO" DCSS is the new FULL-HD / 4K wirelessly controlled satellite TV antenna with 60cm disc to use up to 16 TVs simultaneously. Developed with the dCSS / SCR technology, Mars 4 "NEO" DCSS has been specially manufactured to be used with the dCSS decoders, for example the Sky Q decoders, and to exploit all their features (such as recording a program while watching a other channel). The dCSS technology also has the great advantage of making installation extremely simple and fast thanks to a single cable that comes down from the antenna even for multi-output installations. Like all Glomex "NEO" satellite TV antennas, Mars 4 is equipped with a super fast satellite locking system even in extreme rough sea conditions thanks to totally renewed electronics and mechanics: more powerful processor, faster driver and more robust. Furthermore, the new electronics have been designed to have extremely quiet satellite TV antennas, both in the satellite search phase and in the tracking phase. Thanks to the introduction of a brand new GPS system, the new "NEO" satellite TV antennas save the previous the navigation positions and guarantee increased signal reception performance even at the edges of the signal coverage area. Mars 4 "NEO" is managed through the free Glomex SAT TV App available for iOS and Android devices.

| | | | |
|-------------------|---------------------|--------------------------|---|
| Technology | DVB-sS2 4k FULL HD | LNB frequency range | 10,7 - 12,75 Ghz LNB universal |
| Dish diameter | 600 mm (24") | Radome type | U.V. resistant |
| Radome dimensions | 660x660 mm (26x26") | Power requirement | 12/24 Vdc |
| LNB | Universal single | Operating temp. range | -20° +55° |
| App | Yes | Azimuth | Unlimited |
| Coax cable | 1 | Elevation | 0° / 90° |
| Receiver output | 1/16 | Type of stabilization | Gyro on 2 axis + 3° axis by interpolation |
| Weight | 16 kg (35.3 lb) | Satellite identification | NIT (Network Information Table) |
| Tracking | 50° sec | Min Eirp | 47 dBW |
| Gain | 36,5 db (12 Ghz) | Future Upgrades ready | Yes |
| Dish type | Prime Focus + HPD | Control unit | Unlimited |
| Polarization | Linear (H+V) | | |



By downloading the app, you can manage the "NEO" satellite TV antennas in one click via Bluetooth® with your own smartphone/tablet and:

- update the satellites list
- update the antenna
- select and change satellites
- send the operating parameters of the antenna to technical assistance in case of need.

RE 95207



KIMA TV ANTENNAS

Omnidirectional terrestrial antenna. Excellent for analogic reception and digital terrestrial (with DVB decoder). Radome is in aerodynamic tin with a compact and catchy design. In white ABS for giving maximum resistance to UV. Excellent reception of VHF and UHF frequencies. Possible connection up to 3 TV trough an appropriate splitter. O-Ring included for giving more protection. Against sailly water. Easy placement everywhere thanks to a universal connection at 1"x14. Frequency range: BIII (170 - 230 Mhz) BIV (470 - 606Mhz) BV (606 - 862Mhz). Gain: Band III (22dB) Band IV (25dB) Band V (25dB). Impedance: 75 Ω.

Kit includes:

- 3 F Connectors
- 10 mt of coaxial cable 75Ω
- Supplier with screws
- Fuse holder + fuse
- Key in BS for fixing the cable.

| Supply | Absorption | Antenna dimensions | Supplier dimensions | Gain dB | Weight g | Code |
|----------|------------|--------------------|---------------------|---------|----------|----------|
| 9-30 Vdc | 98-120 mA | Ø 11.5x21cm | 4.7x7.5x3.7cm | 32 | 400 | RE 95163 |



SIGNAL SPLITTER

1 input – 2 outputs
1 input – 4 outputs

RE 95054
RE 95084



KIMA VHF ANTENNAS

A revolutionary antenna with a new shape and technology
Better reception and power in transmission
Useful for reducing the dimensions and with a minimum weight
External radome in tinned ABS. Easy placement everywhere thanks to the universal connection 1"x 14
Cable length: 10mt of coaxial cable 50Ωhm. V.S.W.R.: < 2
Polarization: vertical. Impedance: 50 Ω

| Model | Frequency | Max power | Gain dB | Dimensions cm | Weight g | Code |
|-------|-------------|-----------|---------|---------------|----------|----------|
| VHF | 156-162 MHz | 50 W | 2 | Ø 11.5 x 21 | 450 | RE 95155 |



KIMA VHF- GPS ANTENNAS

A revolutionary antenna with a new shape and technology
Better reception and power in transmission
Useful for reducing the dimensions and with a minimum weight
External radome in tinned ABS. Easy placement everywhere thanks to the universal connection 1"x 14
Polarization: vertical. Impedance: 50 Ω. Coaxial cable 10m 50Ω
GPS: 12 channels - 10mt cable

| Model | Frequency | Max power | Gain dB | Dimensions cm | Weight g | Code |
|-----------|------------|-----------|---------|---------------|----------|----------|
| VHF + GPS | 154-158MHz | 50 W | 2 | Ø 11.5 x 21 | 500 | RE 95156 |



COAXIAL CABLE FOR VHF ANTENNA

Mod RG 58/U, reduction dB/100mt – 50Mhz 10 – 1000 Mhz 57.

| Wires N° | Wire diameter mm | Sheath colour PVC | External diameter mm | Skein weight Kg/100mt | Impedance Ohm | Capacity Pf/m | Length m | Code |
|----------|------------------|-------------------|----------------------|-----------------------|---------------|---------------|----------|----------|
| 1 | 19x0,18 | Black | 5 | 3 | 50 | 98 | 100 | RE 60580 |



COAXIAL CABLE FOR TV Mod RG 58B/U

| Wires N° | Wire diameter mm | Sheath colour PVC | External diameter mm | Skein weight Kg/100m | Impedance Ohm | Length m | Code |
|----------|------------------|-------------------|----------------------|----------------------|---------------|----------|----------|
| 1 | 1 x 0,58 | White | 6 | 3,9 | 75 | 100 | RE 60581 |



WBOAT 5G PLUS ANTENNA

Dual mini sim 5G/WI-FI coastal internet antenna outdoor system for surfing the internet up to 20 miles.

weBBoat® Plus 5G is the new WORLDWIDE* Dual SIM 5G/Wi-Fi All-in-One Plug & Play Coastal internet system to get internet on board and a secure Wi-Fi hotspot inside and outside the boat thanks to the in-built 5G and Wi-Fi antennas for fast connection up to 20 miles from the coast. Now, you have an ultra-fast connection download speed on board: up to 2.5 Gbps. Moreover, if you sail in an area with no 5G signal coverage, the LTE CAT 16 unit allows you to have a 4G connection speed up to 1Gbps. 5G offers a connection with the same level of fibre, but totally wireless and therefore perfect to be used on board. Inside the dome, there are 4 x high performance 5G and 2 x 2.4/5GHz MIMO Wi-Fi antennas for optimizing the speed of data transfers with a huge increase on the connection speed. That means that you can either watch streaming TV chan-

nels and platforms such as Netflix offshore, or work remotely on your boat, using internet connection as like you would be on the mainland.

Equipped with the new revolutionary Glomex MIoT Routerboard platform with a super-powerful processor, that highly increases the connection speed compared to other existing internet systems.

Up to 32 different devices can be used simultaneously without any degradation to the signal or performance. The units built-in advanced switching software allows the user to save money on costly roaming and overage charges by automatically switching to Wi-Fi when available. The WebBoat® Plus 5G is a true Plug & Play device that requires minimal setup and only one power lead for the antenna which operates from 10-30 vDC. The Dual SIM architecture allows the user to have more

choices for operation (i.e. different carriers for coverage, extra data if one card runs out, etc). weBBoat® Plus 5G has additional features such as Carrier aggregation. The new weBBoat® Plus 5G takes advantage of the flexible bandwidth option in LTE and adds the capability to combine multiple bands of the carrier into one big channel. It can access a much bigger data pipe and therefore the achievable data rates improve significantly. Carrier aggregation is supported by improvements to the unit technologies, to make the overall spectrum usage more efficient. automatic APN, SMS management/reading/sending to monitor internet consumption, automatic switching mode with onboard satellite internet devices/V-SAT and an encrypted real-time peer-to-peer connection for remote set-up and service that increase the performance and usefulness of your integrated system Coastal Internet.

TECHNICAL SPECIFICATIONS

- Worldwide unit: for Europe, Middle East, North and South Americas, Australia, New Zealand, Africa and Asia (except for China)
- Antenna dimensions (diam.x H): 250 x 300 mm / 10x12"
- Antenna weight: 1,2 kg / 2,65 lb
- DUAL MINI SIM system
- Inherent antennas: 4 x 5G + 2 x 2.4/5GHz MIMO Wi-Fi antennas
- 5G: Up to 2.5Gbps in download
- LTE CAT16: Up to 1Gbps in download
- WCDMA: Max 42Mbps in download

- CPU: Arm Cortex-A7 800MHz
- RAM: 256MB DDR3
- Automatic switch Wi-Fi registered networks to 4G.
- Automatic APN
- SMS management function
- V-SAT/SAT internet autoswitch mode
- Switching cellular data to external Wi-Fi
- Encrypted real-time peer-to-peerconnection for remote set-up and service
- Power Supply: 10/30 Vdc
- Average Consumption: 150mA

RE 95200



ACCESS POINT FOR METAL/LARGE BOAT

150Mbps Wireless N Nano Router Access point, powered through a micro USB port by an external power adapter or USB connection to a computer. It is designed for use with tablets, smart phones, handheld game consoles and other portable electronic wireless devices.

RE 95201



SWITCH 5-PORT

5-Port 10/100Mbps Desktop Switch.

It provides an easy way to expand your wired network. It can process data at a rate of up to 200Mbps making it an ideal choice for expanding your high performance wired network. Moreover, all ports support Auto MDI/MDIX function, eliminating the need for crossover cables or Uplink ports.

RE 95202



NASHIRA OMNIDIRECTIONAL TV ANTENNA AGC

After more than 25 years of leadership as the best seller TV antenna in the world, the V9112/12 is renewed in design and performance keeping the essential style that is the ideal solution for any type of boat. V9112/12 is also characterized by compact dimensions (diameter 370mm / 14") and high quality materials. Nashira is distinguished by an innovative design based to the new pinnacle as a "shark fin" (high 55mm / 2,2"), for receiving vertically polarized TV signals, that fits perfectly on the new radome with aerodynamic lines. The new reinforced base, coupled with the Glomex exclusive micro-fused, electro-polished and hand polished stainless steel mount (code V9172), ensures the best antenna's stability in any sea conditions. Thanks to vertical pinnacle inside the "shark fin", Nashira can receive polarized TV

signals both horizontally and vertically, thus it is the ideal solution for any type of boat, sailboat or motorboat. The terrestrial signal quality, either analog or digital, can also be tuned by turning the amplifier. This version of Nashira (code V9112/12) is available with 50023/98 amplifier. The 50023/98 is an amplifier provided with by-pass function which, in areas crowded with strong signals, allows to disconnect the amplification and to transmit directly to the TV-set without troubling the reception. If matched with a splitter V9147 (2-ways, optional) installed between the antenna and the amplifier, it can also receive AM-FM radio frequencies.

Antenna diameter 370 mm - Antenna height 240 mm
Base diameter 25 mm - Antenna weight 975 g
Polarization horizontal/vertical - Impedance 75 ohms
Frequency range 40/890 mhz - Gain average 27,5 db
Noise factor 2,1 db - Power consumption 20 ma
Power supply 12/24 vdc - Antenna ampl/by pass: yes
Adjustable gain: yes - Termination "F" female

RE 95001



TALITHA OMNIDIRECTIONAL DVBT TV ANTENNA AGC


Talitha is the Omni-directional TV antenna renewed in design and performance keeping the essential style that is the ideal solution for any type of boat. V9125/12 is also characterized by compact dimensions (diameter 250mm / 10") and high quality materials. Talitha is distinguished by an innovative design based to the new pinnacle as a "shark fin" (high 31 mm / 1,2"), for receiving vertically polarized TV signals, that fits perfectly on the new radome with aerodynamic lines. Thanks to vertical pinnacle inside the "shark fin", Talitha can receive analog or digital

TV signals polarized both horizontally and vertically, thus it is the ideal solution for any type of boat, sailboat or motorboat.

Talitha is equipped with the 50023/98EC amplifier allowing the adjustment of received signal's gain intensity. If matched with a splitter V9147 (2-way, optional) installed between the antenna the antenna and the amplifier, it can also receive AM-FM radio frequencies.

Antenna diameter 250 mm - Antenna height 151 mm
Base diameter 25 mm - Antenna weight 405 g
Polarization horizontal/vertical - Impedance 75 ohms
Frequency range 40/890 mhz - Gain average 26 db
Noise factor 2,2 db - Power consumption 20 ma
Power supply 12/24 vdc - Antenna ampl/by pass: no
Adjustable gain: yes - Termination "F" female

RE 95002



ALTAIR - ANTENNA MARINE TV OMNIDIRECTIONAL AGC

Altair is the omni-directional TV antenna ensuring high performance in signal reception with both polarizations: horizontal and vertical. In fact Altair, is different to the other omni-directional antennas, in that it has a Radome with dimensions (diameter 250 mm/10", height 300 mm/12") allowing the installation of the vertical reception component inside. Altair is equipped with amplifier with by-pass function (50023/98.) In order to keep a balanced look of your boat, Altair can be matched to the VHF RA124, as they are identical in shape and size.

Diameter 250 mm - height 300 mm - Base diameter 25 mm - weight 430 g - Polarization horizontal/vertical
Impedance 75 ohms - Frequency range 40/890 MHz - Gain average 27,5 dB - Noise factor 2,1 dB
Power consumption 25 mA - Power supply 12/24 Vdc - Antenna ampl/by pass: yes - Adjustable gain: yes
Termination "F" female

RE 95003



AVIOR - COMPACT OMNIDIRECTIONAL DVBT TV ANTENNA VT300

Avior is the TV/RADIO FM Omnidirectional antenna in the Glomex range characterized by very compact dimensions (diameter 100 mm/4" and height 210 mm/8"). It enables the user to watch TV programs broadcasted with analog and digital terrestrial system and to listen the radio. The new amplifier allows Avior to have an increase in the gain and to receive vertically and horizontally polarized TV signals coming from more directions at the same time. The inner amplifier, coupled to the power inserter with 2 independent outputs for TV and radio (V91140I-FM), allows the reception of VHF and UHF and FM frequencies with a single antenna. Avior can be installed on any kind of boat, whether sailboat or motorboat, and can be matched to the VHF RA121 antenna.

Diameter 100 mm - height 210 mm - Base diameter 25 mm - weight 250 g - Polarization horizontal/vertical
Impedance 75 ohms - Frequency range 40/890 MHz - Gain average 24,5 dB - Noise factor 1,7 dB
Power consumption 20 mA - Power supply 12 Vdc - Termination "F" female

RE 95004



FIBERGLASS MARINE VHF ANTENNAS FOR SAILBOAT RA106GRPPB



Frequency range: 156-162 Mhz
Gain average: 3 dB
Impedance: 50 ohm
Polarization: vertical
Swr: <1,3 @ 156,8 Mhz

Max input power: 100 W
DC ground: yes
Antenna lenght: 900 mm
Antenna weight: 180 g
Termination: RA106

RE 95106

MARINE VHF ANTENNAS WITH STAINLESS STEEL WHIP FOR SAILBOAT RA106SLSPB



Frequency range: 156-162 Mhz
Gain average: 3 dB
Impedance: 50 ohm
Polarization: vertical
Swr: <1,3 @ 156,8 Mhz

Max input power: 100 W
DC ground: yes
Antenna lenght: 900 mm
Antenna weight: 180 g
Termination: RA106

RE 95105

FIBERGLASS MARINE VHF ANTENNAS FOR SAILBOAT RA106GRPSB18



Frequency range: 156-162 Mhz
Gain average: 3 dB
Impedance: 50 ohm
Polarization: vertical
Swr: <1,3 @ 156,8 Mhz

Max input power: 100 W
DC ground: yes
Antenna lenght: 900 mm
Antenna weight: 180 g
Termination: RA106

RE 95104

MARINE VHF ANTENNAS WITH STAINLESS STEEL WHIP FOR SAILBOAT RA106SLSSB18



Frequency range: 156-162 Mhz
Gain average: 3 dB
Impedance: 50 ohm
Polarization: vertical
Swr: <1,3 @ 156,8 Mhz

Max input power: 100 W
DC ground: yes
Antenna lenght: 900 mm
Antenna weight: 180 g
Termination: RA106

RE 95103

FIBREGLAS MARINE VHF ANTENNA WITH NYLON FERRULE FOR MOTORBOATS RA112



Base in nylon
Frequency range: 156-162 Mhz
Gain average: 3 dB
Impedance: 50 ohm
Polarization: vertical
Swr: <1,3 @ 156,8 Mhz

Max input power: 100 W
Dc ground: yes
Antenna lenght: 1,5 m
Antenna weight: 450 g
Termination: cable

RE 95107

FIBREGLAS MARINE VHF ANTENNA WITH CHROMED FERRULE FOR MOTORBOATS 1206 CR



Base chromed
Frequency range: 156-162 Mhz
Gain average: 3 dB
Impedance: 50 ohm
Polarization: vertical
Swr: <1,3 @ 156,8 Mhz

Max input power: 100 W
Dc ground: yes
Antenna lenght: 2,4 m
Antenna weight: 580 g
Termination: cable

RE 95108



MARINE VHF ANTENNA FOR SAILBOAT AND MOTORBOAT RA111

The REGATTA & EMERGENCY series antennas are characterized by compactness and functionality. RA111 is a small VHF antenna (140mm) protected by a tapered synthetic rubber tube that can be installed, on the sailboats or motorboats. It is equipped with 18m of coaxial cable and with a PL259 male connector.

Frequency range: 156-162 Mhz
Gain average: 1 dB
Impedance: 50 ohm
Polarization: vertical
Swr: <1,3 @ 156,8 Mhz

Max input power: 50 W
Dc ground: no
Antenna lenght: 140 mm
Antenna weight: 220 g
Termination: SO239

RE 95122

MARINE VHF ANTENNA FOR SAILBOAT AND MOTORBOAT RA114

The REGATTA & EMERGENCY series antennas are characterized by compactness and functionality. RA114 is an emergency antenna, to be used in case the main antenna is broken or temporarily idle. This small antenna, only 350mm high, is equipped with 9m of coaxial cable and PL259 male connector.

Frequency range: 156-162 Mhz
Gain average: 1 dB
Impedance: 50 ohm
Polarization: vertical
Swr: <1,3 @ 156,8 Mhz

Max input power: 50 W
Dc ground: no
Antenna lenght: 350 mm
Antenna weight: 900 g
Termination: cable + PL259

RE 95123



MARINE VHF ANTENNA FOR SAILBOAT AND MOTORBOAT RA121

It's a compact VHF antenna (diameter 100 mm, height 210 mm,) conceived for any vessel, whether sailboat or motorboat, and it's provided with all necessary accessories for installation.

Frequency range: 156-162 Mhz
Gain average: 1 dB
Impedance: 50 ohm
Polarization: vertical
Swr: <1,3 @ 156,8 Mhz

Max input power: 50 W
Dc ground: no
Antenna lenght: 210 mm
Antenna weight: 250 g
Termination: SO239

RE 95124



AIS ANTENNA RA110AIS

The Automatic Identification System (AIS) is a monitoring system of naval traffic, useful for navigation safety with difficult meteorological conditions (fog or nocturnal navigation.) The AIS system operates on 2 expressly dedicated VHF channels (161.975 and 162.025 MHz) and allows the user to receive real time information about the traffic in the surrounding area. Glomex has planned and produced a range of calibrated antennas exactly for the specific VHF frequencies and for the AIS standards. The RA111AIS antenna is protected by a tapered synthetic rubber tube and can be installed, on either sailboats or motorboats. Thanks to the V9181 support supplied, the RA111AIS can be installed in a vertical or horizontal position, on the mast or on the pulpit.

Frequency range: 161,975 - 162,025 Mhz
Gain average: 1 dB
Impedance: 50 ohm
Polarization: vertical
Swr: <1,2 @ 156,8 Mhz

Max input power: 50 W
Dc ground: no
Antenna lenght: 140 mm
Antenna weight: 220 g
Termination: SO239

RE 95125

AIS ANTENNA RA110AIS

The Automatic Identification System (AIS) is a monitoring system of naval traffic, useful for navigation safety with difficult meteorological conditions (fog or nocturnal navigation.) The AIS system operates on 2 expressly dedicated VHF channels (161.975 and 162.025 MHz) and allows the user to receive real time information about the traffic in the surrounding area. Glomex has planned and produced a range of calibrated antennas exactly for the specific VHF frequencies and for the AIS standards. The RA110AIS will receive signals on AIS frequencies very efficiently even when the antenna, because of the boat rolling and pitching, is not perfectly vertical. The polished polyurethane paint and the waterproof connector will allow this antenna to maintain an excellent performance for many years.











Frequency range: 161,975 - 162,025 Mhz
Gain average: 3 dB
Impedance: 50 ohm
Polarization: vertical
Swr: <1,2 @ 156,8 Mhz

Max input power: 50 W
Dc ground: no
Antenna lenght: 1 m
Antenna weight: 536 g
Termination: SO239

RE 95126





| | | | | | | | | | | | | | |
|---|---|-------------|----------------|----------|-------------|--------------|----------|-------------|----------------|----------|----------------|-----------------|----------|
|  | <p>AM/FM ANTENNA RA1281 RA1281 is a very solid AM-FM antenna, made of UV resistant synthetic rubber, and is 300mm high. Frequency range: 550 - 1600 KHz / 88 - 108 Mhz - Impedance: 93 ohm Antenna lenght: 300 mm - Antenna weight: 267g - Termination: plug motorola RE 95127</p> | | | | | | | | | | | | |
|  | <p>AM/FM ANTENNA RA128 The RA128 is a 1.5m AM-FM antenna aimed for installation on motorboats and small yachts. Its shape is identical to that of the RA112 (VHF) and RA127 (CB) antennas for a balanced look of your boat. Frequency range: 550 - 1600 KHz / 88 - 108 Mhz - Impedance: 93 ohm Antenna lenght: 1,5 m - Antenna weight: 490g - Termination: SO239 RE 95128</p> | | | | | | | | | | | | |
|  | <p>AM/FM ANTENNA RA1288 The RA1288 is a 2,4m (8') AM-FM antenna aimed for installation on motorboats and large yachts. Frequency range: 550 - 1600 KHz / 88 - 108 Mhz - Impedance: 93 ohm Antenna lenght: 2,4 m - Antenna weight: 600 g - Termination: SO239 RE 95129</p> | | | | | | | | | | | | |
|  | <p>VHF/AM-FM RADIO/AIS SPLITTER RA201 This is the ideal solution for a quick installation of the AIS receiver by taking advantage of the VHF antenna on board. With the RA201 divider, it is in fact possible to switch off the VHF sender and to split the signal received by the VHF antenna between the AM/FM radio and the AIS receiver. Supply: 12 Vdc RE 95130</p> | | | | | | | | | | | | |
|  | <p>MOBILE PHONE ANTENNA RA160 This antenna allow you to send and receive telephone calls with your own mobile phone whilst at sea. Frequency range: 800 - 980 Mhz - Polarization: vertical - Impedance: 50 ohm - Max input power: 100 W Gain average: 6 dB - Dc ground: yes - lenght: 600 mm - weight: 510 g - Termination: N connector RE 95118</p> | | | | | | | | | | | | |
|  | <p>MOBILE PHONE ANTENNA RA161 This antenna allow you to send and receive telephone calls with your own mobile phone whilst at sea. Frequency range: 800 - 980 Mhz - Polarization: vertical - Impedance: 50 ohm - Max input power: 50 W Gain average: 6 dB - Dc ground: yes - lenght: 2,4 m - weight: 742 g - Termination: cable RE 95131</p> | | | | | | | | | | | | |
|  | <p>ORBCOM ANTENNA RA106ORBC The ORBCOMM Communication System takes advantage of low orbit satellites for mobile communications (e-mail, SMS, data.) The RA106 ORBC and RA109 ORBC antennas are designed according to ORBCOMM Italia specifications. Frequency range: tx150 - rx137 Mhz - Polarization: vertical - Impedance: 50 ohm - Gain average: 3 dB Dc ground: yes - lenght: 1 m - weight: 180 g - Termination: RA106 Welded terminal RE 95119</p> | | | | | | | | | | | | |
|  | <p>CB ANTENNA RA127 The Citizens' band, or CB, is a radio frequency band aimed for private communications. This antenna assure a reliable and qualified communication system. Frequency range: 27 Mhz - Polarization: vertical - Impedance: 50 ohm - Swr: < 1,2 Max input power: 50 W - Gain average: 1 dB - Dc ground: no - lenght: 1,5 m - weight: 450 g Termination: cable RE 95143</p> | | | | | | | | | | | | |
|  | <p>CB ANTENNA RA1278 The Citizens' band, or CB, is a radio frequency band aimed for private communications. This antenna assure a reliable and qualified communication system. Frequency range: 27 Mhz - Polarization: vertical - Impedance: 50 ohm - Swr: < 1,2 Max input power: 50 W - Gain average: 1 dB - Dc ground: yes - lenght: 2,4 m - weight: 786 g Termination: cable RE 95145</p> | | | | | | | | | | | | |
|  | <p>FIBREGLASS EXTENSION These are extensions used for vertical elevation of the antenna in order to clear the reception/transmission field. They can be made of stainless steel or UV resistant fibreglass and are the ideal complement to all Glomex (VHF, AIS, etc.) antennas.</p> <table border="0" style="width: 100%;"> <tr> <td>Model RA150</td> <td>- lenght 2,4 m</td> <td style="text-align: right;">RE 95150</td> </tr> <tr> <td>Model RA120</td> <td>- lenght 2 m</td> <td style="text-align: right;">RE 95151</td> </tr> <tr> <td>Model RA149</td> <td>- lenght 1,2 m</td> <td style="text-align: right;">RE 95152</td> </tr> <tr> <td>Model RA122/60</td> <td>- lenght 600 mm</td> <td style="text-align: right;">RE 95153</td> </tr> </table> | Model RA150 | - lenght 2,4 m | RE 95150 | Model RA120 | - lenght 2 m | RE 95151 | Model RA149 | - lenght 1,2 m | RE 95152 | Model RA122/60 | - lenght 600 mm | RE 95153 |
| Model RA150 | - lenght 2,4 m | RE 95150 | | | | | | | | | | | |
| Model RA120 | - lenght 2 m | RE 95151 | | | | | | | | | | | |
| Model RA149 | - lenght 1,2 m | RE 95152 | | | | | | | | | | | |
| Model RA122/60 | - lenght 600 mm | RE 95153 | | | | | | | | | | | |

ANTENNAS ACCESSORIES



| | | |
|---|---|-----------------|
|  | <p>MOUNT RA115 4 way ratchet mount in reinforced nylon UV resistant design with handle, for deck or bulkhead. Hole for GPS and feed-thru for coax cable. Usable with antennas no longer than 9' in self supporting mode. Standard 1"x14 thread.</p> | <p>RE 95115</p> |
|  | <p>MOUNT RA135 4 way ratchet mount in reinforced nylon UV resistant design with knob, for deck or bulkhead. Hole for GPS and feed-thru for coax cable. Usable with antennas no longer than 8' in self supporting mode. Standard 1"x14 thread. New waterproof feed-thru for a very easy passage of the cable.</p> | <p>RE 95116</p> |
|  | <p>MOUNT RA107SS 4 way ratchet mount polished stainless steel design with clamp, for deck or bulkhead. Hole for GPS and feed-thru for coax cable. Standard 1"x14 thread.</p> | <p>RE 95164</p> |
|  | <p>MOUNT RA116SS Heavy duty 4 way ratchet mount polished stainless steel design with handle, for deck or bulkhead. Hole for GPS and feed-thru for coax cable. Standard 1"x14 thread.</p> | <p>RE 95133</p> |
|  | <p>MOUNT RA166/00 4 way ratchet mount polished stainless steel design with handle, for deck or bulkhead. Hole for GPS and feed-thru for coax cable. Usable with antennas no longer than 9' in self supporting mode. Standard 1"x14 thread.</p> | <p>RE 95165</p> |
|  | <p>MOUNT V9174 Universal mount stainless steel for antennas and extensions. Standard thread 1"x14, weight 10 oz (280 g), height 4" (100 mm).</p> | <p>RE 95166</p> |
|  | <p>MOUNT V9175OT Universal mount reinforced nylon for GPS antennas only. Usable with RA129 extension. Standard thread 1"x14, weight 1 oz (27 g), height 13/8" (40 mm).</p> | <p>RE 95136</p> |
|  | <p>MOUNT RA134 Rail ratchet mount in reinforced nylon UV resistant, design with knob and hole for GPS. Easy installation on vertical or horizontal rails of 7/8" (22 mm) and 1" (25 mm). Usable with antennas no longer than 8' in self supporting mode. Standard 1"x14 thread.</p> | <p>RE 95168</p> |
|  | <p>MOUNT V9175 Universal mount reinforced nylon for GPS antennas only. Usable with RA129 extension. Standard thread 1"x14, weight 2 oz (50 g), height 4" (100 mm).</p> | <p>RE 95169</p> |

ANTENNAS ACCESSORIES



| | | |
|--|---|-----------------|
| | <p>MOUNT RA119 Stand-off bracket reinforced nylon. For bulkhead and rail of Ø 1" (25 mm) and 1"1/4 (30 mm). It accepts Ø 38,5 mm. (1,5") antennas and is supplied with plastic inserts for extensions diam. 1" (25 mm), 1" 1/8 (28 mm) and 1"1/4 (30 mm).</p> | <p>RE 95170</p> |
| | <p>MOUNT RA145 Rail mount reinforced nylon UV resistant, for installation of GPS antennas on horizontal rails of 7/8" (22 mm) and 1" (25 mm). Usable with RA129 extension. Standard 1"x14 thread.</p> | <p>RE 95171</p> |
| | <p>MOUNT RA175 Rail mount reinforced nylon UV resistant, for installation of GPS antennas only on horizontal rails of 7/8" (22 mm), 1" (25 mm) and 1"1/4 (30 mm). Supplied with clamps for all 3 rail diameters.</p> | <p>RE 95172</p> |
| | <p>MOUNT RA165 Rail ratchet mount stainless steel electropolished, design with handle and hole for GPS. Easily installation on vertical or horizontal rails of 7/8" (22 mm) and 1" (25 mm). Usable with antennas no longer than 8' in self supporting mode. Standard 1"x14 thread.</p> | <p>RE 95173</p> |
| | <p>MOUNT V9173 Masthead racket stainless steel. Thread 1"x14, weight 12 oz (330 g)</p> | <p>RE 95174</p> |
| | <p>CONNECTOR RA131 PL259 male connector for RG213/U 50 ohm</p> | <p>RE 95070</p> |
| | <p>CONNECTOR RA132 PL259 male connector for RG58/U 50 ohm</p> | <p>RE 95073</p> |
| | <p>CONNECTOR RA133 PL258 double female connector for PL259 50 ohm</p> | <p>RE 95078</p> |
| | <p>CONNECTOR V9144 Male F connector for RG59/U 75 ohm</p> | <p>RE 95074</p> |
| | <p>CONNECTOR RA163 F/F female connector 75 ohm</p> | <p>RE 95075</p> |
| | <p>CONNECTOR RA156 TNC male connector for RG58/U 50 ohm</p> | <p>RE 95083</p> |

NMEA 2000® CABLES

GARMIN®

The NMEA network protocol was developed in the 1980s by the National Marine Electronics Association with the aim of offering a uniform standard for data transmission between devices of different types and from different manufacturers. For example, GPS, wind, depth, AIS, speed, engine and compass data can be transmitted between various Simrad, Garmin and Raymarine devices. For this purpose, however, a NMEA2000 interface is required on the related devices. The images, such as those of the radar and echo sounder, but also the contents of the maps, cannot be transmitted via the NMEA2000® protocol.



NMEA 2000® CABLE EXTENSIONS

- 2 meter extension cable (6 ft)
- 4 meter extension cable (13 ft)
- 6 meter extension cable (19 ft)
- 10 meter extension cable (32 ft)

RE 83075
RE 83076
RE 83077
RE 83078



NMEA 2000® MULTI-PORT T-CONNECTOR

Make NMEA 2000 installations easier with our multi-port T-connector. This solution creates a more robust NMEA 2000 backbone by reducing issues with breaking points as well as stress induced by long back bones. The rigid construction is less prone to failure and decreases installation time.

RE 83079



4-PIN FEMALE TO 5-PIN MALE NMEA 2000® ADAPTER CABLE

Connect your compatible echoMAP™ CHIRP or ECHOMAP Plus chartplotter/sounder combo to a NMEA 2000 network with this 6 foot (2 meters) adapter cable.

RE 83080



NMEA 2000® WEATHER CAP

Our weather cap protects the connector on your NMEA 2000 cable from the harsh marine environment.

RE 83081



NMEA 2000® POWER ISOLATOR

Use our power isolator to ensure sources that could power the bus are separated properly during installation of the NMEA 2000 network.


RE83082



NMEA 2000® STARTER KIT

Our starter kit has everything you need to build a basic NMEA 2000 network on your boat. The kit includes an NMEA 2000 drop cable (2 m), backbone cable (6 m), power cable (2 m), 2 T- connectors, and male and female terminator connectors.

RE 83083



NMEA 2000® POWER CABLE

Supply power to your NMEA 2000 network with our 2 meter (6 ft) power cable.

RE 83084



FUSION® RA70 SERIES MARINE STEREO

The RA70 Series from Fusion® comprises three DIN-sized marine stereos, designed to deliver quality audio entertainment experiences on the water at value-packed price points.

| Dimensions mm | Weight | Supply | Power Rms | Bluetooth® | Amplifier | Speakerph. | Code |
|---------------|--------|------------|-----------|------------|-----------|------------|----------|
| 60x188x123,5 | 556 g | 10,8-16VCC | 4x26 W | 2,4 GHz | AB class | Yes | RE 83036 |

All RA70 Series stereos contain:

DIN mounting plate - Four 8-gauge, self-tapping screws - Power and speaker wiring harness
Auxiliary-in, line-out, and subwoofer-out wiring harnesses - Documentation



FUSION® MS-RA210 MARINE STEREO

The MS-RA210 compact marine stereo from Fusion® features a modern design aesthetic and built-in DSP technology for an optimized audio entertainment experience.

| Dimensions mm | Weight | Supply | Power Rms | Bluetooth® | Amplifier | Speakerph. | Code |
|---------------|--------|------------|-----------|------------|-----------|------------|----------|
| 68x157x126,6 | 350 g | 10,8-16VCC | 4x26 W | 2,4 GHz | D Class | Yes | RE 83037 |

Package contents:

Fusion MS-RA210 marine stereo - Mounting gasket - Four 6-gauge, self-tapping screws
Two screw covers - Power and speaker wiring harness - Auxiliary-in, line-out, and subwoofer-out wiring harnesses - 2 meter (6 ft) NMEA 2000® drop cable - 6 ft (2 meter) NMEA 2000 drop cable - Documentation



FUSION® MS-RA60 MARINE STEREO

The MS-RA60 is modern, compact and the most economical marine stereo from Fusion® yet.

| Dimensions mm | Weight | Supply | Power Rms | Bluetooth® | Amplifier | Speakerph. | Code |
|----------------|--------|------------|-----------|------------|-----------|------------|----------|
| 68x156,9x103,2 | 316 g | 10,8-16VCC | 4x22 W | 2,4 GHz | D Class | Yes | RE 83038 |

Package contents:

Fusion MS-RA60 marine stereo - Mounting gasket - Four 6-gauge, self-tapping screws - Two screw covers
Power and speaker wiring harness - Auxiliary-in, line-out, and subwoofer-out wiring harnesses - Documentation



FUSION® BB100 BLACK BOX

The Fusion MS-BB100 is a compact, value packed black box entertainment solution designed to save space at the helm.

| Dimensions mm | Weight | Supply | Power Rms | Bluetooth® | Amplifier | Speakerph. | Code |
|----------------|--------|------------|-----------|------------|-----------|------------|----------|
| 68x156,9x103,2 | 316 g | 10,8-16VCC | 4x22 W | 2,4 GHz | D Class | Yes | RE 83039 |

Package contents:

MS-BB100 media black box - IPX7 wired remote control - One remote control mounting nut (M56)
One remote control mounting gasket - Four 8-gauge, mounting screws - Power and speaker wiring harness
Auxiliary-in, line-out, and subwoofer-out wiring harness - 6 ft (2 meter) NMEA 2000® drop cable
Documentation



APOLLO™ SERIES



ONE-PIECE GLASS TOUCH DISPLAY

The premium glass touchscreen display is beautiful edge-to-edge. Simply tap or swipe the screen for stereo control without the hassle of trying to locate the right button.

FUSION® RA770



DESIGNED AND ENGINEERED TO TRUE-MARINE™ STANDARDS

Built on the True-Marine design philosophy from Fusion®, the Apollo RA770 stereo has an IPX6 and IPX7 rated water resistant front panel and has been tested to a high level of protection against salt, fog, temperature, vibration and UV.

MODERN DESIGN AND AESTHETICS

Providing uniformity across the helm, the brilliantly designed black front face blends seamlessly into black glass panels, complementing other electronics and MFDs for a tidy, uniform and elegant installation.

| Dimensions mm | Weight | Supply | Power | Bluetooth® | Amplifier | Speakerph. | Protection | Code |
|---------------|--------|---------------|--|------------|-----------|------------|--------------------------------|----------|
| 82x192 x119,4 | 750 g | 10,8 - 16V CC | 4x43W rms (2 Ohm) 4x26W rms (4 Ohm) | 2,4 GHz | D Class | Yes | IPX6 / IPX7 (front panel only) | RE 83040 |



FREEDOM OF CHOICE TO LISTEN TO WHAT YOU WANT

Take advantage of the many source options available, including AirPlay 2 feature1, BLUETOOTH® technology, UPnP1, optical audio, advanced SiriusXM® features, DAB+ radio, AM/FM radio, AUX and USB connections.

FUSION® RA670



DESIGNED AND ENGINEERED TO TRUE-MARINE™ STANDARDS

Built on the True-Marine design philosophy from Fusion®, the Apollo RA670 stereo has an IPX6 and IPX7 rated water resistant front panel and has been tested to a high level of protection against salt, fog, temperature, vibration and UV.

MODERN DESIGN AND AESTHETICS

Providing uniformity across the helm, the brilliantly designed black front face blends seamlessly into black glass panels, complementing other electronics and MFDs for a tidy, uniform and elegant installation.

| Dimensions mm | Weight | Supply | Power | Bluetooth® | Amplifier | Speakerph. | Protection | Code |
|---------------|--------|---------------|--|------------|-----------|------------|--------------------------------|----------|
| 82x192 x119,4 | 750 g | 10,8 - 16V CC | 4x43W rms (2 Ohm) 4x26W rms (4 Ohm) | 2,4 GHz | D Class | Yes | IPX6 / IPX7 (front panel only) | RE 83041 |



FUSION® WB670



DESIGNED AND ENGINEERED TO TRUE-MARINE™ STANDARDS

Built on the True-Marine design philosophy from Fusion®, the Apollo WB670 stereo has been tested to a high level of protection against salt, fog, temperature, vibration and UV.

COMPACT DESIGN

Designed to save space at the helm, Apollo WB670 can be hidden away in the dash or mounted in a variety of areas such as storage lockers, inside helm consoles and other concealed compartments.

| Dimensions mm | Weight | Supply | Power | Bluetooth® | Amplifier | Protection | Code |
|---------------|--------|---------------|--|------------|-----------|--------------------------------|----------|
| 130x130x55 | 475 g | 10,8 - 16V CC | 4x43W rms (2 Ohm) 4x26W rms (4 Ohm) | 2,4 GHz | D Class | IPX6 / IPX7 (front panel only) | RE 83042 |



FUSION® ARX WIRELESS REMOTE

Enjoy the freedom to control your audio entertainment from anywhere around your boat with the ARX wireless remote. Whether you're fishing at the transom or about to jump from the swim platform into the water – audio control is within reach any time, anywhere.

| Dimensions | Weight | Battery type | Wireless range | Radio frequency | Operating temp. | Protection | Code |
|------------|--------|--------------|----------------|-----------------|------------------|------------|----------|
| 65x10,8 mm | 30 g | CR2032 | 10 m | 2,4 GHz | from 0° to 50° C | IPX6/IPX7 | RE 83043 |



AMAGNETIC SPEAKER

Splash-proof and saline resistant
Grille reinforced white ABS and corrosion resistant - Stainless steel screw included



| Model | Dimensions mm | Impedance | Max power RMS | Max power peak | Inlet hole mm | Max thickness mm | Code |
|-------|---------------|-----------|---------------|----------------|---------------|------------------|---------|
| 2 vie | Ø 135 | 4 ohm | 30 W | 60 W | Ø 104 | 54 | RE83016 |
| 2 vie | Ø 150 | 4 ohm | 40 W | 80 W | Ø 114 | 56 | RE83017 |
| 2 vie | Ø 185 | 4 ohm | 50 W | 100 W | Ø 134 | 65 | RE83018 |



FUSION® SIGNATURE SERIES 3 MARINE SPEAKERS

Pushing the boundaries of what is possible on the water, the new revamped Signature Series 3 marine speakers deliver unparalleled performance even when exposed to harsh marine environments.



| Model | Dimensions mm | Nominal impedance | Max power Rms | Max power peak | Inlet hole mm | Max depth mm | Code |
|----------|---------------|-------------------|---------------|----------------|---------------|--------------|----------|
| SG-F652W | Ø 200x103 | 4 ohms | 75 W | 230 W | Ø 136 | 79 | RE 83001 |
| SG-F772W | Ø 220x109,5 | 4 ohms | 100 W | 280 W | Ø 156 | 86 | RE 83002 |
| SG-F882W | Ø 247x131,5 | 4 ohms | 130 W | 330 W | Ø 188 | 106 | RE 83003 |



FUSION® XS SERIES MARINE SPEAKERS

Enjoy high-performance acoustics, enhanced protection from the environment all at a midrange price point with the XS Series speakers from Fusion.



| Model | Dimensions mm | Nominal impedance | Max power Rms | Max power peak | Inlet hole mm | Max depth mm | Code |
|-----------|---------------|-------------------|---------------|----------------|---------------|--------------|----------|
| XS-F40CWB | Ø 135x68 | 4 ohms | 30 W | 120 W | Ø 99 | 54 | RE 83004 |
| XS-F65CWB | Ø 177x81 | 4 ohms | 50 W | 200 W | Ø 135 | 67 | RE 83005 |
| XS-F77CWB | Ø 196x94 | 4 ohms | 60 W | 240 W | Ø 162 | 77 | RE 83006 |



FUSION® FM SERIES MARINE SPEAKERS

The Fusion FM Series speakers are engineered to deliver quality acoustics to your boat and have a sleek and minimalistic aesthetic to match modern boat design trends.



| Model | Dimensions mm | Nominal impedance | Max power Rms | Max power peak | Inlet hole mm | Max depth mm | Code |
|----------|---------------|-------------------|---------------|----------------|---------------|--------------|----------|
| FM-F65SW | 153x153x69,6 | 4 ohms | 30 W | 120 W | 138x138 | 70 | RE 83007 |
| FM-F77SW | 181x181x82,9 | 4 ohms | 50 W | 200 W | 165x165 | 83 | RE 83008 |

MARINE SPEAKERS ACCESSORIES



FUSION® APOLLO™ MARINE AMPLIFIERS

These efficient, easy-to-install amplifiers work with your compatible Fusion stereo system and let you choose from monoblock, multichannel and zone amplifier options.



FUSION® SERIE APOLLO™ MS-AP4

4 Channel Marine Amplifier (150 watt RMS per Channel)

| Channels | Operating voltage | Peak power | RMS power (2 ohm) | RMS power (4 ohm) | Amplifier | Dimensions mm (DxLxH) | Code |
|----------|-------------------|------------|-------------------|-------------------|-----------|-----------------------|----------|
| 4 | 10,8-16V DC | 1200 W | 4x290 W | 4x150 W | D Class | 62x231,6x235 | RE 83009 |



FUSION® SERIE APOLLO™ MS-AP6

6 Channel Marine Amplifier (150 watt RMS per Channel)

| Channels | Operating voltage | Peak power | RMS power (2 ohm) | RMS power (4 ohm) | Amplifier | Dimensions mm (DxLxH) | Code |
|----------|-------------------|------------|-------------------|-------------------|-----------|-----------------------|----------|
| 6 | 10,8-16V DC | 1800 W | 6x290 W | 6x150 W | D Class | 62x297x229,3 | RE 83010 |



FUSION® SERIE APOLLO™ MS-AP8

8 Channel Marine Amplifier (150 watt RMS per Channel)

| Channels | Operating voltage | Peak power | RMS power (2 ohm) | RMS power (4 ohm) | Amplifier | Dimensions mm (DxLxH) | Code |
|----------|-------------------|------------|-------------------|-------------------|-----------|-----------------------|----------|
| 8 | 10,8-16V DC | 2400 W | 8x290 W | 8x150 W | D Class | 62x359x229 | RE 83011 |



PROTECTION BOX

Water and salt resistant.
Front panel in polycarbonate.
Automatic soft opening.
Plastic cover.
Easy to install.

RE 83023



DOCK FOR IPOD/MP3/IPHONE

Water, salt and corrosion resistant.
Amplifier included.
Mounting bracket included.

RE 83022



PROTECTION BOX

Resistant to collisions, UV, fully watertight, dark grey pleaxiglass, advanced design.
Spring closure with cover (there is a gasket for making it completely waterproof).
Dimensions: 231x 102 x 50 mm.

RE 83045